




ASL Environmental
Sciences

Ice Profiling SonarTM (IPS)



© www.sednaepic.com – Jill Heinerth

An upward-looking sonar device, mounted above the ocean floor to accurately measure ice draft.



Applications

In order to estimate ice forces, production rates, and mass balances, accurate measurements of ice thickness are essential. The Ice Profiling Sonar (IPS)TM makes those measurements much easier to obtain for applications in:

- Offshore Oil Platforms
- Design of Coastal Structures
- Research Oceanography
- Bridges and Causeways
- Global Warming Studies
- Pipeline Studies.

Features

- The IPSTM has been the proven instrument of choice for ice researchers since 1996.
- Pressure sensor: Paroscientific Digiquartz 2000 series, with long term stability and 0.01% full scale accuracy.
- Excellent horizontal resolution using a high frequency 420 kHz transducer with narrow 0.9° half-beam width.
- Very low power consumption enables continuous sampling at ping rates of 1-2 seconds over one year or more.



The IPS instrument was originally developed by Dr. H. Melling of the Institute of Ocean Sciences, DFO Canada. Since then ASL has made ongoing upgrades to the design and features of the instrument.



ASL Environmental
Sciences

ASL Environmental Sciences
#1-6703 Rajpur Place
V8M 1Z5 Saanichton, BC
Canada

Phone: +1250-656-0177

Email: asl@aslenv.com

Website: aslenv.com



Ice Profiling Sonar (IPS)TM

Features (continued)

- Multiple sampling options within a deployment to accommodate seasonal changes (up to 12 phases).
- Ocean wave monitoring capability using interleaved 2 Hz burst sampling.
- Windows-based software for deployment planning, initialization, testing and data downloading.
- Full digitized echo can be stored to 1 cm resolution.
- Target detection thresholds are user configurable with up to 5 targets stored.

Model IPS5 Specifications

UPWARD LOOKING SONAR

Operating Frequency	420 kHz
Beam Width	0.9° (center beam to half power point)
Sampling Rate	up to 2 Hz (continuous or burst)
Duty Cycle	up to 100%
Range	175 m (ice), up to 225 m (water)
Accuracy of Ice Draft	± 0.05 m *
Resolution	0.01 m
Gain	4 levels

REALTIME CLOCK

Accuracy	± 5 min/year
----------	--------------

DATA STORAGE

Standard	8 GB Compact Flash
Optional	up to 16 GB Compact Flash

POWER

Provides more than 52 weeks at
1 Hz sampling

TILT SENSOR

Range	± 20°
Accuracy	± 0.5°
Precision	0.01°

TEMPERATURE SENSOR

Accuracy	± 0.1°C
Resolution	0.05°C

PRESSURE SENSOR

Paroscientific Digiquartz [®] 2000 series	
Range	0 - 126 m
Resolution	0.003 m
Accuracy	0.01% full scale (other ranges available)

SIZE

0.17 m diameter x 1.0 m length

* Assumes variations in sound speed and density are accounted for.

SOFTWARE The following Windows-based software is included in the IPSTM package:

IPS5Link	Communications software to enable setup and download functions.
IPS5Extract	Utility package for extracting raw binary data files (available upon request).

OPTIONAL FEATURES

Short housing which can be powered by an external battery or by an external power source.

Extended alkaline battery pack or carrier for Lithium battery packs to extend deployment duration.

The IPSTM is also available in a version designed for river applications which includes an RS 422 serial connection for real time data and remote power - Shallow Water Ice ProfilerTM (SWIP).

Custom versions of the IPSTM are also available for Autonomous Underwater Vehicles (AUV).

Both taut line and gimballed bottom mount moorings available.

